




**G19 Globe
GX5.3 / GU5.3**



Working Voltage 12V AC/DC
Weight 0.9 oz. (25 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
E26 / 24 (US)**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
E26 / 27 (EURO)**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
GU10 / GZ10**



Working Voltage 100 - 240V AC
Weight 1.42 oz. (40 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
E11**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
E12 (US)**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
E12 (EURO)**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
E17**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
E14 (US)**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
E14 (EURO)**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
B22D**



Working Voltage 100 - 240V AC
Weight 1.7 oz. (48 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



**G19 Globe
EZ10**



Working Voltage 12V AC/DC
Weight 1.4 oz. (38 g)
Operating Temp -20°C to +40°C
Lumen Maintenance 30,000 hours
Warranty 3 Years Limited



G19 Globe



G19 Globe
BA15S



Working Voltage	12V AC/DC	Optional : AC Adapter
Weight	1.7 oz. (48 g)	
Operating Temp	-20°C to +40°C	
Lumen Maintenance	30,000 hours	
Warranty	3 Years Limited	



G19 Globe
BA15D




Working Voltage	12V AC/DC 100 - 240V AC	Optional : AC Adapter
Weight	1.7 oz. (48 g)	
Operating Temp	-20°C to +40°C	
Lumen Maintenance	30,000 hours	
Warranty	3 Years Limited	

LAMP LUMINOUS FLUX

All Lamp Luminous Flux Data are Indicated in Max Values


V6 series

Chipsets	CREE® LEDs MT-G
Power Consumption	7 Watts
True White	CRI 75 530 lm
Natural White	CRI 80 460 lm
Warm White	CRI 80 405 lm




V5 series

Chipsets	LUXEON® Rebel ES	CREE® LEDs XP-G
Power Consumption	7 Watts	7 Watts
True White	CRI 80 410 lm	470 lm
Natural White	CRI 80 380 lm	415 lm
Warm White	CRI 80 340 lm	360 lm
	CRI 90 275 lm	-



Chipsets	OSRAM OSOLON® SSL 150 LED
Power Consumption	7 Watts
True White	CRI 70 410 lm
Natural White	CRI 82 350 lm
Warm White	CRI 82 300 lm
	CRI 95 275 lm




LAMP LUMINOUS FLUX

All Lamp Luminous Flux Data are Indicated in Max Values


V4 series

Chipsets	LUXEON® Rebel	CREE® LEDs XP-C
Power Consumption	7 Watts	7 Watts
True White	CRI 80 360 lm	355 lm
Natural White	CRI 80 360 lm	330 lm
Warm White	CRI 80 275 lm	270 lm
	CRI 90 220 lm	-
Red	130 lm	-
Green	320 lm	-
Blue	100 lm	-




V3 series

Chipsets	LUXEON® Rebel	CREE® LEDs MC-E	CREE® LEDs XM-L
Power Consumption	1 Watt	3 Watts	7 Watts
True White	CRI 80 95 lm	160 lm	420 lm
Natural White	CRI 80 95 lm	160 lm	360 lm
Warm White	CRI 80 55 lm	95 lm	300 lm
	CRI 90 45 lm	60 lm	-
Red	35 lm	60 lm	-
Green	80 lm	150 lm	-
Blue	25 lm	45 lm	-




V2 series

Chipsets	EPISTAR
Power Consumption	7 Watts
True White	CRI 75 250 lm
	CRI 90 195 lm
Natural White	CRI 75 250 lm
	CRI 90 195 lm
Warm White	CRI 75 185 lm
	CRI 90 160 lm




V1 series

Chipsets	EPISTAR	
Power Consumption	5 Watts	7 Watts
True White	CRI 70 185 lm	210 lm
	CRI 90 150 lm	170 lm
Natural White	CRI 70 185 lm	210 lm
	CRI 90 150 lm	170 lm
Warm White	CRI 70 125 lm	160 lm
	CRI 90 100 lm	115 lm
Red	60 lm	70 lm
Green	70 lm	85 lm
Blue	35 lm	40 lm



BEAM ANGLE



COLOR

